



(1)標準仕様 主ジブ定格総荷重

単位 (ton)

1 2 ton カウンタウエイト 取付時				
ジブ長さ (m) 作業半径 (m)	9.97	16.67	23.37	30.07
3.0	55.00	28.00	22.00	14.00
3.5	50.00	28.00	22.00	14.00
4.0	42.50	28.00	22.00	14.00
4.5	36.50	28.00	22.00	14.00
5.0	31.65	28.00	22.00	14.00
5.5	26.90	26.65	22.00	14.00
6.0	23.35	23.10	22.00	14.00
6.5	20.55	20.30	20.15	14.00
7.0	18.25	18.00	17.85	13.50
7.5	12.50	16.15	16.00	13.00
8.0		14.60	14.45	12.50
8.5		13.30	13.15	12.00
9.0		12.30	12.00	11.50
9.5		11.25	11.00	11.00
10.0		10.40	10.15	10.70
11.0		9.00	8.70	9.20
12.0		7.80	7.55	8.05
13.0		6.80	6.60	7.10
14.0		6.00	5.80	6.25
14.2		5.80	5.65	6.10
15.0			5.10	5.60
16.0			4.55	5.00
17.0			4.05	4.50
18.0			3.60	4.05
19.0			3.25	3.65
20.0			2.90	3.30
20.9			2.60	3.05
22.0				2.75
24.0				2.20
26.0				1.75
27.6				1.45
最大ジブ角度	62°	74°	79°	81°
最小ジブ角度	0°	0°	0°	0°